



- NOTE: 1) HYDRO @ 390 PSIG. MIN.
 2) ALL NPT ARE SA-182-304 S.S.
 3) UHA-51 (e)(2) NO IMPACT TESTING.

SHELL / HEADS		16-VD-30-R	
.1875" SA-240-304 S.S. 2:1 S.E.		REV. 12-26-13	
JOGGLE - .159 OFFSET		304 S.S. DATE: 10-22-10	
		FOR: HANSON STANDARD	
.1875" SA-240-304 S.S.		VERT. AIR TANK	
		SURFACE AREA = 14.7 SQ. FT.	
		INSIDE: UNPAINTED - PASSIVATE	
M.A.W.P.	300 PSIG. @ 200 °F	OUTSIDE: BEAD BLAST & PASSIVATE	
M.D.M.T.	-155 °F @ 300 PSIG.	CAD-"B" SIZED UNDER "STD"-SERIES	
ASME. SECTION VIII	DIV. 1, 2013	BY: J.G. SCALE: 1"=12"	
X-RAY:	RT-NO	ROY E. HANSON JR. MFG.	
GALLONS:	30	1600 E. WASHINGTON BLVD.	
	WT. 137 LBS.	LOS ANGELES, CA 90021	
SERIAL NO.			
N.B. NO.			