



NOTE: 1) HYDRO @ 375 PSIG. MIN.  
 2) D.T. = 6.3"  
 3) 4:1 SAFETY SPEC. MC-331

SHELL / HEADS		205" SA-455 2:1 S.E.	
JOGGLE		205" SA-455	
		.200" SA-455	
		(.189" MIN.)	
M.A.W.P.	250 PSIG. @ 200' F	PA-898-B	REV. 8-13-13
M.D.M.T.	-20' F @ 250 PSIG.	FOR:	DATE: 8-12-13
ASME: SECTION VIII	DIV. 1, 2010 ADD 2011	HORIZ. PROPANE TANK	
X-RAY: RT-4 SPOT L.S. ONLY		SURFACE AREA = 52.9 SQ. FT.	
GALLONS: 175	WT. 550 LBS.	1390.0 C.F.M. REG'D (NOTE: 2)	
SERIAL NO.	N.B.	INSIDE: UNPAINTED, DEHYDRATED	
		OUTSIDE: PRIME	
		BY: J.G./B.C.	SCALE: 1"=12"
		<b>ROY E. HANSON JR. MFG.</b>	
		1600 E. WASHINGTON BLVD.	
		LOS ANGELES, CA 90021	

ROLL GUARD PER  
 PA-775-B-1A